



EFFICIENT AND RELIABLE FIREWOOD PROCESSOR FOR BIG LOGS WITH SMALL INVESTMENT

the 43 Pro, the Hakki Pilke 43 is a starter model with fewer features, offering a robust and efficient firewood processor ideal for those needing a reliable machine for processing large logs on a smaller scale. As a streamlined version of the 43 Pro, this model retains the essential performance features while delivering the same high processing speed.

With 15 tons of splitting force, the 43 easily handles logs up to 43 cm in diame-

Built with the same bullet-proof design as ter, splitting them into up to 12 pieces, or even 16 with soft wood. The HakkiSplit™ system, adapted from the 43 Pro, ensures fast and consistent splitting, automatically adjusting force as needed. The hydraulic log clamp and joystick-controlled HakkiCut™ system make cutting safe and efficient, allowing the entire cutting process to be managed with a single button press.

> Equipped with a cleaning outfeed conveyor, the machine automatically separates

debris from firewood during processing, significantly reducing the need for additional cleaning equipment. The 43 also includes a control valve for accessories, making it easy to integrate additional equipment like HakkiFeed log tables.

Designed for easy maintenance, the 43 requires minimal upkeep. Thanks to its hydraulic functions, the machine operates without V-belts, ensuring reliable performance and reducing the need for frequent maintenance.

RELIABLE PROCESSOR FOR OCCASIONAL FIREWOOD PROCESSING

- ► HYDRAULIC HEIGHT ADJUSTMENT OF THE SPLITTING BLADE
- ► AC 10 AUTOMATIC CHAIN TENSIONER
- ► HYDRAULIC LOG CLAMP

- ► VARIOS SPLITTING BLADES AVAILABLE
- ► HALF-STROKE SPLITTING FUNCTION
- ► ERGONOMIC CONTROL PANEL AND JOYTSICK SAWING
- ► CLEANING OUTFEED CONVEYOR
- ► SAFETY COVERS AND SYSTEMS TO ENSURE **USER SAFETY**
- ► FIRST-RATE PRODUCTIVITY

TECHNICAL SPECIFICATIONS

Max log diameter	430 mm	17"
Max log length	600 mm	24"
Maximum splitting power	15 t	
Cutting Bar lenght	18" (Harvester)	
Power source	PTO, electric	
Splitting blade	2/6-way	
Outfeed conveyor length	4 m	13′1″
Infeed conveyor length	2.5 m	8'

STANDARD EQUIPMENT

Infeed serial connection kit
Accessory valve
Hydraulic infeed conveyor
Infeed guide plate
Hydraulic log clamp
Safety cover
AC10 automatic chain tensioner (hydraulic)
HakkiCut™ cutting control
Automatically optimised cutting speed
Electic automatic chain oil lubrication
Hydraulically retracting log measuring device
Half-stroke splitting function
HakkiSplit [™] delay-free splitting (3 speeds)
Hydraulic height adjustment of the splitting blade
Cleaning outfeed conveyor
Pivoting outfeed conveyor (manual)
Outfeed conveyor speed control

OPTIONAL EQUIPMENT

2/4, 8, 12-way 16-way for soft wood	
1 m	3'3"
	16-way f

ACCESSORIES

HakkiFeed	372, 422, 471, 472
HakkiLift	431
Hakki Pilke Cleaner	
Hakki Pilke Roller	
Power Unit	

DIMENSIONS IN TRANSPORT POSITION

Height	2 560 mm	8'5"
Length	2 540 mm	8'4"
Width	1 400 mm	4'7"
Weight	1 300 kg	2 866 lbs

ERGONOMIC CONTROLS

The machine's functions can be easily controlled with the ergonomic and easyto-use control panel. An unparalleled user interface which enables you to process firewood with just two buttons.



AUTOMATIC CHAIN TENSIONER AND HYDRAULIC LOG CLAMP

The AC 10 automatic chain tensioner maintains optimal saw chain tension at all times. The chain can be conveniently replaced after releasing chain tension with the lever pictured - no tools required! The powerful hydraulic log clamp holds the log securely in place for steady and precise processing.



WIDE RANGE OF SPLITTING BLADES

Equipped with a wide range of optional splitting blades, the machine can handle logs of various sizes, featuring up to a 12-way splitting knife or even 16-way with soft wood to produce high quality firewood every time.



CLEANING OUTFEED CONVEYOR

The 43 comes standard with a cleaning outfeed conveyor. A groove at the end of the conveyor efficiently separates debris from the firewood, allowing it to be easily collected and repurposed

